2. ANEXO. CÓDIGO FUENTE DEL PROTOTIPO DE PLATAFORMA DE GESITÓN DE PROYECTOS DE ADQUISIÓN DE SERVIDUMBRES PETROLERAS.

A continuación, se presentan el código fuente del prototipo de la plataforma de gestión:

DEUSTERRA

1. APP
1.1. HTTP
1.1.1. CONTROLLERS
1.1.1.1. AUTH

- **Confirmpaswordcontroller.php**

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Providers\RouteServiceProvider;
use Illuminate\Foundation\Auth\ConfirmsPasswords;

class ConfirmPasswordController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Confirm Password Controller
    |--------------------------------------------------------------------------
    |
    | This controller is responsible for handling password confirmations and
    | uses a simple trait to include the behavior. You're free to explore
    | this trait and override any functions that require customization.
    |
    */

    use ConfirmsPasswords;

    /**
     * Where to redirect users when the intended url fails.
     *
     * @var string
     */
    protected $redirectTo = RouteServiceProvider::HOME;

    /**
```

```
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('auth');
    }
}
```

- **Forgotpaswordcontroller.php**

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Foundation\Auth\SendsPasswordResetEmails;

class ForgotPasswordController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Password Reset Controller
    |--------------------------------------------------------------------------
    |
    | This controller is responsible for handling password reset emails and
    | includes a trait which assists in sending these notifications from
    | your application to your users. Feel free to explore this trait.
    |
    */

    use SendsPasswordResetEmails;
}
```

- Logincontroller.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Providers\RouteServiceProvider;
use Illuminate\Foundation\Auth\AuthenticatesUsers;

class LoginController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Login Controller
    |--------------------------------------------------------------------------
    |
    | This controller handles authenticating users for the application and
    | redirecting them to your home screen. The controller uses a trait
    | to conveniently provide its functionality to your applications.
```

```
    |
    */

    use AuthenticatesUsers;

    /**
     * Where to redirect users after login.
     *
     * @var string
     */
    protected $redirectTo = RouteServiceProvider::HOME;

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('guest')->except('logout');
    }
}
```

- Registrercontroller.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Providers\RouteServiceProvider;
use App\Models\User;
use Illuminate\Foundation\Auth\RegistersUsers;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Validator;

class RegisterController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Register Controller
    |--------------------------------------------------------------------------
    |
    | This controller handles the registration of new users as well as their
    | validation and creation. By default this controller uses a trait to
    | provide this functionality without requiring any additional code.
    |
    */

    use RegistersUsers;

    /**
```

```
     * Where to redirect users after registration.
     *
     * @var string
     */
    protected $redirectTo = RouteServiceProvider::HOME;

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('guest');
    }

    /**
     * Get a validator for an incoming registration request.
     *
     * @param  array  $data
     * @return \Illuminate\Contracts\Validation\Validator
     */
    protected function validator(array $data)
    {
        return Validator::make($data, [
            'name' => ['required', 'string', 'max:255'],
            'email' => ['required', 'string', 'email', 'max:255',
'unique:users'],
            'password' => ['required', 'string', 'min:8', 'confirmed'],
        ]);
    }

    /**
     * Create a new user instance after a valid registration.
     *
     * @param  array  $data
     * @return \App\Models\User
     */
    protected function create(array $data)
    {
        return User::create([
            'name' => $data['name'],
            'email' => $data['email'],
            'password' => Hash::make($data['password']),
        ]);
    }
}
```

- ResetPaswordCotroller.php

```
<?php

namespace App\Http\Controllers\Auth;
```

```
use App\Http\Controllers\Controller;
use App\Providers\RouteServiceProvider;
use Illuminate\Foundation\Auth\ResetsPasswords;

class ResetPasswordController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Password Reset Controller
    |--------------------------------------------------------------------------
    |
    | This controller is responsible for handling password reset requests
    | and uses a simple trait to include this behavior. You're free to
    | explore this trait and override any methods you wish to tweak.
    |
    */

    use ResetsPasswords;

    /**
     * Where to redirect users after resetting their password.
     *
     * @var string
     */
    protected $redirectTo = RouteServiceProvider::HOME;
}
```

- VerificacionContoller.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Providers\RouteServiceProvider;
use Illuminate\Foundation\Auth\VerifiesEmails;

class VerificationController extends Controller
{
    /*
    |--------------------------------------------------------------------------
    | Email Verification Controller
    |--------------------------------------------------------------------------
    |
    | This controller is responsible for handling email verification for any
    | user that recently registered with the application. Emails may also
    | be re-sent if the user didn't receive the original email message.
    |
    */

    use VerifiesEmails;

    /**
     * Where to redirect users after verification.
     *
```

```
     * @var string
     */
    protected $redirectTo = RouteServiceProvider::HOME;

    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('auth');
        $this->middleware('signed')->only('verify');
        $this->middleware('throttle:6,1')->only('verify', 'resend');
    }
}
```

1.1.1.2. CUSTOM

- **CurrencyHelpers.php**

```
<?php

namespace App\Http\Controllers\Custom;

class CurrencyHelpers {
    public static $sign = '$';
    public static $thousandsSeparator = ',';
    public static $decimalSeparator = '.';

    public static function numberToCurrency($number){

        $number = number_format((float)$number, 2, '.', '');
        $startPosition = strlen($number);
        $decimalPosition = strpos($number,CurrencyHelpers::$decimalSeparator);
        if($decimalPosition > 0){
            $startPosition = $decimalPosition;
        }
        $currentPosition = $startPosition - 3;
        while ($currentPosition >=1) {
            $left = substr($number,0,$currentPosition);
            $right = substr($number,$currentPosition,(strlen($number) -
$currentPosition));
            $number = $left.CurrencyHelpers::$thousandsSeparator.$right;
            $currentPosition = $currentPosition -3;
        }
        $number = CurrencyHelpers::$sign.$number;
        return $number;
    }
    public static function currencyToNumber($value){
        $value = str_replace(CurrencyHelpers::$sign, "",$value);
        $value = str_replace(CurrencyHelpers::$thousandsSeparator, "",$value);
```

```
        $value = str_replace(" ", "",$value);
        $value = doubleval($value);
        return $value;
    }
}
```

- Appbasecontroller.php

```
<?php

namespace App\Http\Controllers;

use InfyOm\Generator\Utils\ResponseUtil;
use Response;

/**
 * @SWG\Swagger(
 *   basePath="/api/v1",
 *   @SWG\Info(
 *     title="Laravel Generator APIs",
 *     version="1.0.0",
 *   )
 * )
 * This class should be parent class for other API controllers
 * Class AppBaseController
 */
class AppBaseController extends Controller
{
    public function sendResponse($result, $message)
    {
        return Response::json(ResponseUtil::makeResponse($message, $result));
    }

    public function sendError($error, $code = 404)
    {
        return Response::json(ResponseUtil::makeError($error), $code);
    }

    public function sendSuccess($message)
    {
        return Response::json([
            'success' => true,
            'message' => $message
        ], 200);
    }
}
```

- Controller.php

```
<?php

namespace App\Http\Controllers;
```

```
use Illuminate\Foundation\Auth\Access\AuthorizesRequests;
use Illuminate\Foundation\Bus\DispatchesJobs;
use Illuminate\Foundation\Validation\ValidatesRequests;
use Illuminate\Routing\Controller as BaseController;

class Controller extends BaseController
{
    use AuthorizesRequests, DispatchesJobs, ValidatesRequests;
}
```

- Homecontroller.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class HomeController extends Controller
{
    /**
     * Create a new controller instance.
     *
     * @return void
     */
    public function __construct()
    {
        $this->middleware('auth');
    }

    /**
     * Show the application dashboard.
     *
     * @return \Illuminate\Http\Response
     */
    public function index()
    {
        return view('home');
    }
}
```

- Projectcontroller.php

```
<?php

namespace App\Http\Controllers;

use App\DataTables\ProjectDataTable;
use App\Http\Requests;
use App\Http\Requests\CreateProjectRequest;
```

```
use App\Http\Requests\UpdateProjectRequest;
use App\Repositories\ProjectRepository;
use Flash;
use App\Http\Controllers\AppBaseController;
use Response;
use Auth;
use Storage;
use App\Models\Project;

class ProjectController extends AppBaseController
{
    /** @var  ProjectRepository */
    private $projectRepository;

    public function __construct(ProjectRepository $projectRepo)
    {
        $this->projectRepository = $projectRepo;
    }

    /**
     * Display a listing of the Project.
     *
     * @param ProjectDataTable $projectDataTable
     * @return Response
     */
    public function index(ProjectDataTable $projectDataTable)
    {
        return $projectDataTable->render('projects.index');
    }

    /**
     * Show the form for creating a new Project.
     *
     * @return Response
     */
    public function create()
    {
        return view('projects.create');
    }

    /**
     * Store a newly created Project in storage.
     *
     * @param CreateProjectRequest $request
     *
     * @return Response
     */
    public function store(CreateProjectRequest $request)
    {
        $input = $request->all();
        $input['responsible'] = Auth::user()->id;
        $input['pdt'] = '';
        if (!!$request->file('pdt')) {
```

```
            $filelink = $request->file('pdt')-
>storeAs('public/Proyectos/'.$request->name, $request->file('pdt')-
>getClientOriginalName());
            $input['pdt'] = $filelink;
        }
        $project = $this->projectRepository->create($input);

        Flash::success('Project saved successfully.');

        return redirect(route('projects.index'));
    }

    /**
     * Display the specified Project.
     *
     * @param  int $id
     *
     * @return Response
     */
    public function show($id)
    {
        $project = $this->projectRepository->find($id);
        if (empty($project)) {
            Flash::error('Project not found');

            return redirect(route('projects.index'));
        }

        return view('projects.show')->with('project', $project);
    }

    /**
     * Show the form for editing the specified Project.
     *
     * @param  int $id
     *
     * @return Response
     */
    public function edit($id)
    {
        $project = $this->projectRepository->find($id);

        if (empty($project)) {
            Flash::error('Project not found');

            return redirect(route('projects.index'));
        }

        return view('projects.edit')->with('project', $project);
    }

    /**
     * Update the specified Project in storage.
     *
     * @param  int              $id
```

```
     * @param UpdateProjectRequest $request
     *
     * @return Response
     */
    public function update($id, UpdateProjectRequest $request)
    {
        $project = $this->projectRepository->find($id);

        if (empty($project)) {
            Flash::error('Project not found');

            return redirect(route('projects.index'));
        }
        $input = $request->all();
        $input['responsible'] = Auth::user()->id;
        if (!!$request->file('pdt')) {
            $filelink = $request->file('pdt')-
>storeAs('public/Proyectos/'.$request->name, $request->file('pdt')-
>getClientOriginalName());
            $input['pdt'] = $filelink;
        }

        $project = $this->projectRepository->update($input, $id);

        Flash::success('Project updated successfully.');

        return redirect(route('projects.index'));
    }

    /**
     * Remove the specified Project from storage.
     *
     * @param  int $id
     *
     * @return Response
     */
    public function destroy($id)
    {
        $project = $this->projectRepository->find($id);

        if (empty($project)) {
            Flash::error('Project not found');

            return redirect(route('projects.index'));
        }

        $this->projectRepository->delete($id);

        Flash::success('Project deleted successfully.');

        return redirect(route('projects.index'));
    }
}
```

- Propertycontroller.php

```
<?php

namespace App\Http\Controllers;

use App\DataTables\PropertyDataTable;
use App\Http\Requests;
use App\Http\Requests\CreatePropertyRequest;
use App\Http\Requests\UpdatePropertyRequest;
use App\Http\Requests\AddDocumentsPropertyRequest;
use App\Repositories\PropertyRepository;
use Flash;
use App\Http\Controllers\AppBaseController;
use Response;
use App\Models\Project;
use App\Models\Property;

class PropertyController extends AppBaseController
{
    /** @var  PropertyRepository */
    private $propertyRepository;

    public function __construct(PropertyRepository $propertyRepo)
    {
        $this->propertyRepository = $propertyRepo;
    }

    /**
     * Display a listing of the Property.
     *
     * @param PropertyDataTable $propertyDataTable
     * @return Response
     */
    public function index($project)
    {
        $propertyDataTable = new PropertyDataTable($project);
        return $propertyDataTable->render('properties.index', ['project' =>
$project]);
    }

    /**
     * Show the form for creating a new Property.
     *
     * @return Response
     */
    public function create($project)
    {
        return view('properties.create', ['project' => $project]);
    }

    /**
     * Store a newly created Property in storage.
     *
```

```
     * @param CreatePropertyRequest $request
     *
     * @return Response
     */
    public function store(CreatePropertyRequest $request)
    {
        $project = Project::find($request->project)->name;
        $input = $request->all();
        $input['field_report'] = '';
        if (!!$request->file('field_report')) {
            $filelink = $request->file('field_report')-
>storeAs('public/Proyectos/'.$project, $request->file('field_report')-
>getClientOriginalName());
            $input['field_report'] = $filelink;
        }
        $input['map'] = '';
        if (!!$request->file('map')) {
            $filelink = $request->file('map')-
>storeAs('public/Proyectos/'.$project, $request->file('map')-
>getClientOriginalName());
            $input['map'] = $filelink;
        }
        $property = $this->propertyRepository->create($input);

        Flash::success('Property saved successfully.');

        return redirect(route('properties.index', $property->project));
    }

    /**
     * Display the specified Property.
     *
     * @param  int $id
     *
     * @return Response
     */
    public function show($id)
    {
        $property = $this->propertyRepository->find($id);
        if (empty($property)) {
            Flash::error('Property not found');

            return redirect(route('properties.index'));
        }

        return view('properties.show')->with('property', $property);
    }

    /**
     * Show the form for editing the specified Property.
     *
     * @param  int $id
     *
     * @return Response
     */
```

```
    public function edit($id)
    {
        $property = $this->propertyRepository->find($id);

        if (empty($property)) {
            Flash::error('Property not found');

            return redirect(route('properties.index'));
        }

        return view('properties.edit')->with('property', $property);
    }

    /**
     * Update the specified Property in storage.
     *
     * @param  int              $id
     * @param UpdatePropertyRequest $request
     *
     * @return Response
     */
    public function update($id, UpdatePropertyRequest $request)
    {
        $property = $this->propertyRepository->find($id);

        if (empty($property)) {
            Flash::error('Property not found');

            return redirect(route('properties.index'));
        }
        $project = $property->associated_project->name;
        $input = $request->all();
        if (!!$request->file('field_report')) {
            $filelink = $request->file('field_report')-
>storeAs('public/Proyectos/'.$project, $request->file('field_report')-
>getClientOriginalName());
            $input['field_report'] = $filelink;
        }
        if (!!$request->file('map')) {
            $filelink = $request->file('map')-
>storeAs('public/Proyectos/'.$project, $request->file('map')-
>getClientOriginalName());
            $input['map'] = $filelink;
        }

        $property = $this->propertyRepository->update($input, $id);

        Flash::success('Property updated successfully.');

        return redirect(route('properties.index', $property->project));
    }

    private function validateCompletion(Property $property) {
        $study = $property->study ? true : false;
        $workad = $property->workad ? true : false;
```

```
        $inventory = $property->inventory ? true : false;
        $act = $property->act ? true : false;
        $act_payment = $property->act_payment ? true : false;
        $easement = $property->easement ? true : false;
        $easement_payment = $property->easement_payment ? true : false;
        $imposition = $property->imposition ? true : false;
        $imposition_payment = $property->imposition_payment ? true : false;

        return $study && $workad && $inventory && (($act && $easement &&
$act_payment && $easement_payment) || ($imposition && $imposition_payment));
    }

    public function addDocuments($id, AddDocumentsPropertyRequest $request)
    {
        $property = $this->propertyRepository->find($id);

        if (empty($property)) {
            Flash::error('Property not found');

            return redirect(route('properties.index'));
        }
        $project = $property->associated_project->name;
        $input = $request->all();

        if (!!$request->file('study')) {
            $filelink = $request->file('study')-
>storeAs('public/Proyectos/'.$project, $request->file('study')-
>getClientOriginalName());
            $input['study'] = $filelink;
            $input['study_date'] = date("Y-m-d");
        }

        if (!!$request->file('workad')) {
            $filelink = $request->file('workad')-
>storeAs('public/Proyectos/'.$project, $request->file('workad')-
>getClientOriginalName());
            $input['workad'] = $filelink;
            $input['workad_date'] = date("Y-m-d");
        }

        if (!!$request->file('inventory')) {
            $filelink = $request->file('inventory')-
>storeAs('public/Proyectos/'.$project, $request->file('inventory')-
>getClientOriginalName());
            $input['inventory'] = $filelink;
            $input['inventory_date'] = date("Y-m-d");
        }

        if (!!$request->file('act')) {
            $filelink = $request->file('act')-
>storeAs('public/Proyectos/'.$project, $request->file('act')-
>getClientOriginalName());
            $input['act'] = $filelink;
            $input['act_date'] = date("Y-m-d");
        }
```

```
        if (!!$request->file('act_payment')) {
            $filelink = $request->file('act_payment')-
>storeAs('public/Proyectos/'.$project, $request->file('act_payment')-
>getClientOriginalName());
            $input['act_payment'] = $filelink;
        }

        if (!!$request->file('easement')) {
            $filelink = $request->file('easement')-
>storeAs('public/Proyectos/'.$project, $request->file('easement')-
>getClientOriginalName());
            $input['easement'] = $filelink;
            $input['easement_date'] = date("Y-m-d");
        }

        if (!!$request->file('easement_payment')) {
            $filelink = $request->file('easement_payment')-
>storeAs('public/Proyectos/'.$project, $request->file('easement_payment')-
>getClientOriginalName());
            $input['easement_payment'] = $filelink;
        }

        if (!!$request->file('imposition')) {
            $filelink = $request->file('imposition')-
>storeAs('public/Proyectos/'.$project, $request->file('imposition')-
>getClientOriginalName());
            $input['imposition'] = $filelink;
            $input['imposition_date'] = date("Y-m-d");
        }

        if (!!$request->file('imposition_payment')) {
            $filelink = $request->file('imposition_payment')-
>storeAs('public/Proyectos/'.$project, $request->file('imposition_payment')-
>getClientOriginalName());
            $input['imposition_payment'] = $filelink;
        }



        $property = $this->propertyRepository->update($input, $id);

        $property_completed = $this->validateCompletion($property);

        if($property_completed) {
            $property->status = 'Finalizado';
            $property->save();
            $properties = Property::where('project', $property->project);
            $project_completed = true;
            foreach($properties as $p) {
                if($p->status == 'En Gestión'){
                    $project_completed = false;
                }
            }
            if($project_completed) {
```

```
                $project = Project::find($property->project);
                $project->status = 'Finalizado';
                $project->save();
            }
        }

        Flash::success('Property updated successfully.');

        return redirect(route('properties.show', $property->id));
    }

    /**
     * Remove the specified Property from storage.
     *
     * @param  int $id
     *
     * @return Response
     */
    public function destroy($id)
    {
        $property = $this->propertyRepository->find($id);

        if (empty($property)) {
            Flash::error('Property not found');

            return redirect(route('properties.index'));
        }

        $this->propertyRepository->delete($id);

        Flash::success('Property deleted successfully.');

        return redirect(route('properties.index', $property->project));
    }
}
```

1.1.2. MIDDLEWARE

- **Authenticate.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Auth\Middleware\Authenticate as Middleware;

class Authenticate extends Middleware
{
    /**
     * Get the path the user should be redirected to when they are not
authenticated.
     *
     * @param  \Illuminate\Http\Request  $request
     * @return string|null
```

```
     */
    protected function redirectTo($request)
    {
        if (! $request->expectsJson()) {
            return route('login');
        }
    }
}
```

- **Encrypcookies.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Cookie\Middleware\EncryptCookies as Middleware;

class EncryptCookies extends Middleware
{
    /**
     * The names of the cookies that should not be encrypted.
     *
     * @var array
     */
    protected $except = [
        //
    ];
}
```

- **Preventrequestduringmaintnance.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Foundation\Http\Middleware\PreventRequestsDuringMaintenance as
Middleware;

class PreventRequestsDuringMaintenance extends Middleware
{
    /**
     * The URIs that should be reachable while maintenance mode is enabled.
     *
     * @var array
     */
    protected $except = [
        //
    ];
}
```

- **Redirectifaunthenticated.php**

```
<?php

namespace App\Http\Middleware;

use App\Providers\RouteServiceProvider;
use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;

class RedirectIfAuthenticated
{
    /**
     * Handle an incoming request.
     *
     * @param  \Illuminate\Http\Request  $request
     * @param  \Closure  $next
     * @param  string|null  ...$guards
     * @return mixed
     */
    public function handle(Request $request, Closure $next, ...$guards)
    {
        $guards = empty($guards) ? [null] : $guards;

        foreach ($guards as $guard) {
            if (Auth::guard($guard)->check()) {
                return redirect(RouteServiceProvider::HOME);
            }
        }

        return $next($request);
    }
}
```

- **TrimStrings.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Foundation\Http\Middleware\TrimStrings as Middleware;

class TrimStrings extends Middleware
{
    /**
     * The names of the attributes that should not be trimmed.
     *
     * @var array
     */
    protected $except = [
```

```
        'password',
        'password_confirmation',
    ];
}
```

- **TrustHost.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Http\Middleware\TrustHosts as Middleware;

class TrustHosts extends Middleware
{
    /**
     * Get the host patterns that should be trusted.
     *
     * @return array
     */
    public function hosts()
    {
        return [
            $this->allSubdomainsOfApplicationUrl(),
        ];
    }
}
```

- **TrustProxies.php**

```
<?php

namespace App\Http\Middleware;

use Fideloper\Proxy\TrustProxies as Middleware;
use Illuminate\Http\Request;

class TrustProxies extends Middleware
{
    /**
     * The trusted proxies for this application.
     *
     * @var array|string|null
     */
    protected $proxies;

    /**
     * The headers that should be used to detect proxies.
     *
     * @var int
     */
    protected $headers = Request::HEADER_X_FORWARDED_ALL;
}
```

- **VerifyCsrgtoken.php**

```
<?php

namespace App\Http\Middleware;

use Illuminate\Foundation\Http\Middleware\VerifyCsrfToken as Middleware;

class VerifyCsrfToken extends Middleware
{
    /**
     * The URIs that should be excluded from CSRF verification.
     *
     * @var array
     */
    protected $except = [
        //
    ];
}
```

1.1.3. REQUEST

- **AddDocumentsPropertyRequest.php**

```
namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use App\Models\Property;

class AddDocumentsPropertyRequest extends FormRequest
{

    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        $rules = [];

        return $rules;
```

```
    }
}
```

- **CreateProjectRequest.php**

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use App\Models\Project;

class CreateProjectRequest extends FormRequest
{

    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return Project::$rules;
    }
}
```

- **CreatePropertyRequest.php**

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use App\Models\Property;

class CreatePropertyRequest extends FormRequest
{

    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
```

```
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        return Property::$rules;
    }
}
```

- **UpdateProjectRequest.php**

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use App\Models\Project;

class UpdateProjectRequest extends FormRequest
{

    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        // $rules = Project::$rules;
        $rules = [];

        return $rules;
    }
}
```

- **UpdatePropertyRequest.php**

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;
use App\Models\Property;

class UpdatePropertyRequest extends FormRequest
{

    /**
     * Determine if the user is authorized to make this request.
     *
     * @return bool
     */
    public function authorize()
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array
     */
    public function rules()
    {
        $rules = Property::$rules;

        return $rules;
    }
}
```

- **Kernel.php**

```
<?php

namespace App\Http;

use Illuminate\Foundation\Http\Kernel as HttpKernel;

class Kernel extends HttpKernel
{
    /**
     * The application's global HTTP middleware stack.
     *
     * These middleware are run during every request to your application.
     *
     * @var array
     */
    protected $middleware = [
```

```
        // \App\Http\Middleware\TrustHosts::class,
        \App\Http\Middleware\TrustProxies::class,
        \Fruitcake\Cors\HandleCors::class,
        \App\Http\Middleware\PreventRequestsDuringMaintenance::class,
        \Illuminate\Foundation\Http\Middleware\ValidatePostSize::class,
        \App\Http\Middleware\TrimStrings::class,
        \Illuminate\Foundation\Http\Middleware\ConvertEmptyStringsToNull::class,
    ];

    /**
     * The application's route middleware groups.
     *
     * @var array
     */
    protected $middlewareGroups = [
        'web' => [
            \App\Http\Middleware\EncryptCookies::class,
            \Illuminate\Cookie\Middleware\AddQueuedCookiesToResponse::class,
            \Illuminate\Session\Middleware\StartSession::class,
            // \Illuminate\Session\Middleware\AuthenticateSession::class,
            \Illuminate\View\Middleware\ShareErrorsFromSession::class,
            \App\Http\Middleware\VerifyCsrfToken::class,
            \Illuminate\Routing\Middleware\SubstituteBindings::class,
        ],

        'api' => [
            'throttle:api',
            \Illuminate\Routing\Middleware\SubstituteBindings::class,
        ],
    ];

    /**
     * The application's route middleware.
     *
     * These middleware may be assigned to groups or used individually.
     *
     * @var array
     */
    protected $routeMiddleware = [
        'auth' => \App\Http\Middleware\Authenticate::class,
        'auth.basic' =>
\Illuminate\Auth\Middleware\AuthenticateWithBasicAuth::class,
        'cache.headers' => \Illuminate\Http\Middleware\SetCacheHeaders::class,
        'can' => \Illuminate\Auth\Middleware\Authorize::class,
        'guest' => \App\Http\Middleware\RedirectIfAuthenticated::class,
        'password.confirm' =>
\Illuminate\Auth\Middleware\RequirePassword::class,
        'signed' => \Illuminate\Routing\Middleware\ValidateSignature::class,
        'throttle' => \Illuminate\Routing\Middleware\ThrottleRequests::class,
        'verified' => \Illuminate\Auth\Middleware\EnsureEmailIsVerified::class,
    ];
}
```

2. MODELS

- **Project.php.**

```
<?php

namespace App\Models;

use Eloquent as Model;
use Illuminate\Database\Eloquent\SoftDeletes;
use Illuminate\Database\Eloquent\Factories\HasFactory;

/**
 * Class Project
 * @package App\Models
 * @version April 28, 2021, 4:05 am UTC
 *
 * @property \App\Models\User $responsible
 * @property string $name
 * @property integer $responsible
 * @property string $pdt
 * @property string $status
 */
class Project extends Model
{
    use SoftDeletes;

    use HasFactory;

    public $table = 'projects';


    protected $dates = ['deleted_at'];



    public $fillable = [
        'name',
        'responsible',
        'pdt',
        'status'
    ];

    /**
     * The attributes that should be casted to native types.
     *
     * @var array
     */
    protected $casts = [
        'id' => 'integer',
        'name' => 'string',
        'responsible' => 'integer',
        'pdt' => 'string',
        'status' => 'string'
    ];
```

```
    /**
     * Validation rules
     *
     * @var array
     */
    public static $rules = [
        'name' => 'required',
        'pdt' => 'required',
        'status' => 'required'
    ];

    /**
     * @return \Illuminate\Database\Eloquent\Relations\BelongsTo
     **/
    public function responsible()
    {
        return $this->belongsTo(\App\Models\User::class, 'responsible', 'id');
    }
    public function properties()
    {
        return $this->hasMany(\App\Models\Property::class, 'project');
    }
}
```

- **Property.php**

```
<?php

namespace App\Models;

use Eloquent as Model;
use Illuminate\Database\Eloquent\SoftDeletes;
use Illuminate\Database\Eloquent\Factories\HasFactory;

/**
 * Class Property
 * @package App\Models
 * @version May 2, 2021, 2:46 pm UTC
 *
 * @property \App\Models\Project $project
 * @property string $name
 * @property integer $project
 * @property string $idsig
 * @property string $field_report
 * @property string $map
 * @property string $status
 */
class Property extends Model
{
    use SoftDeletes;

    use HasFactory;

    public $table = 'properties';
```

```
protected $dates = ['deleted_at'];



public $fillable = [
    'name',
    'project',
    'idsig',
    'field_report',
    'map',
    'status',
    'study',
    'study_date',
    'viability',
    'workad',
    'workad_date',
    'direct_agreement',
    'inventory',
    'inventory_date',
    'act',
    'act_date',
    'act_value',
    'act_payment',
    'act_payment_date',
    'easement',
    'easement_date',
    'easement_value',
    'easement_payment',
    'easement_payment_date',
    'imposition',
    'imposition_date',
    'imposition_value',
    'imposition_payment',
    'imposition_payment_date',
];

/**
 * The attributes that should be casted to native types.
 *
 * @var array
 */
protected $casts = [
    'id' => 'integer',
    'name' => 'string',
    'project' => 'integer',
    'idsig' => 'string',
    'field_report' => 'string',
    'map' => 'string',
    'status' => 'string',
    'study' => 'string',
    'study_date' => 'date',
    'viability' => 'string',
    'workad' => 'string',
```

```
        'workad_date' => 'date',
        'direct_agreement' => 'string',
        'inventory' => 'string',
        'inventory_date' => 'date',
        'act' => 'string',
        'act_date' => 'date',
        'act_value' => 'integer',
        'act_payment' => 'string',
        'act_payment_date' => 'date',
        'easement' => 'string',
        'easement_date' => 'date',
        'easement_value' => 'integer',
        'easement_payment' => 'string',
        'easement_payment_date' => 'date',
        'imposition' => 'string',
        'imposition_date' => 'date',
        'imposition_value' => 'integer',
        'imposition_payment' => 'string',
        'imposition_payment_date' => 'date',
    ];

    /**
     * Validation rules
     *
     * @var array
     */
    public static $rules = [
        'name' => 'required',
        'project' => 'required',
        'idsig' => 'required',
        'status' => 'required'
    ];

    /**
     * @return \Illuminate\Database\Eloquent\Relations\BelongsTo
     **/
    public function associated_project()
    {
        return $this->belongsTo(\App\Models\Project::class, 'project', 'id');
    }
}
```

- **User.php**

```
<?php

namespace App\Models;

use Illuminate\Contracts\Auth\MustVerifyEmail;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

class User extends Authenticatable
```

```
{
    use HasFactory, Notifiable;

    /**
     * The attributes that are mass assignable.
     *
     * @var array
     */
    protected $fillable = [
        'name',
        'email',
        'password',
    ];

    /**
     * The attributes that should be hidden for arrays.
     *
     * @var array
     */
    protected $hidden = [
        'password',
        'remember_token',
    ];

    /**
     * The attributes that should be cast to native types.
     *
     * @var array
     */
    protected $casts = [
        'email_verified_at' => 'datetime',
    ];
}
```

3. RESOURCES

3.1. VIEWS

3.1.1 AUTH

3.1.1.1 Emails

- **Pasword.blade.php**

```
Click here to reset your password: <a href="{{ $link = url('password/reset',
$token).'?email='.urlencode($user->getEmailForPasswordReset()) }}"> {{ $link }}
</a>
```

3.1.1.2 Paswords

- **Confirm.blade.php**

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <title>{{ config('app.name') }}</title>
```

```
    <!-- Tell the browser to be responsive to screen width -->
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport">

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.11.2/css/all.min.css"
          integrity="sha512-
0S+nbAYis87iX26mmj/+fWt1MmaKCv80H+Mbo+Ne7ES4I6rxswpfnC6PxmLiw33Ywj2ghbtTw0FkLbMW
qh4F7Q=="
          crossorigin="anonymous"/>

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <!-- HTML5 Shim and Respond.js IE8 support of HTML5 elements and media
queries -->
    <!-- WARNING: Respond.js doesn't work if you view the page via file:// -->
    <!--[if lt IE 9]>
    <script
src="https://oss.maxcdn.com/html5shiv/3.7.3/html5shiv.min.js"></script>
    <script src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js"></script>
    <![endif]-->

</head>
<body class="hold-transition login-page">
<div class="login-box">
    <div class="login-logo">
        <a href="{{ url('/home') }}"><b>{{ config('app.name') }}</b></a>
    </div>

    <div class="card">
        <div class="card-body login-card-body">
            <p class="login-box-msg">Please confirm your password before
continuing.</p>

            <form method="POST" action="{{ route('password.confirm') }}">
                @csrf

                <div class="input-group mb-3">
                    <input type="password"
```

```
                            name="password"
                            class="form-control @error('password') is-invalid
@enderror"
                            placeholder="Password"
                            required autocomplete="current-password">
                        <div class="input-group-append">
                            <div class="input-group-text"><span class="fas fa-
lock"></span></div>
                        </div>
                        @error('password')
                        <span class="error invalid-feedback">{{ $message }}</span>
                        @enderror
                    </div>


                    <div class="row">
                        <div class="col-12">
                            <button type="submit" class="btn btn-primary btn-
block">Confirm Password</button>
                        </div>
                        <!-- /.col -->
                    </div>
                </form>

                <p class="mt-3 mb-1">
                    <a href="{{ route('password.request') }}">Forgot Your
Password?</a>
                </p>
            </div>
            <!-- /.login-card-body -->
        </div>

</div>
<!-- /.login-box -->

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

</body>
</html>
```

- **Email.blade.php**

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <title>{{ config('app.name') }}</title>
```

```
    <!-- Tell the browser to be responsive to screen width -->
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport">

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.11.2/css/all.min.css"
          integrity="sha512-
0S+nbAYis87iX26mmj/+fWt1MmaKCv80H+Mbo+Ne7ES4I6rxswpfnC6PxmLiw33Ywj2ghbtTw0FkLbMW
qh4F7Q=="
          crossorigin="anonymous"/>

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <!-- HTML5 Shim and Respond.js IE8 support of HTML5 elements and media
queries -->
    <!-- WARNING: Respond.js doesn't work if you view the page via file:// -->
    <!--[if lt IE 9]>
    <script
src="https://oss.maxcdn.com/html5shiv/3.7.3/html5shiv.min.js"></script>
    <script src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js"></script>
    <![endif]-->

</head>
<body class="hold-transition login-page">
<div class="login-box">
    <div class="login-logo">
        <a href="{{ url('/home') }}"><b>{{ config('app.name') }}</b></a>
    </div>

    <!-- /.login-logo -->
    <div class="card">
        <div class="card-body login-card-body">
            <p class="login-box-msg">You forgot your password? Here you can
easily retrieve a new password.</p>

            @if (session('status'))
                <div class="alert alert-success">
                    {{ session('status') }}
                </div>
```

```
            @endif

            <form action="{{ route('password.email') }}" method="post">
                @csrf

                <div class="input-group mb-3">
                    <input type="email"
                           name="email"
                           class="form-control @error('email') is-invalid
@enderror"
                           placeholder="Email">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
envelope"></span></div>
                    </div>
                    @error('email')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="row">
                    <div class="col-12">
                        <button type="submit" class="btn btn-primary btn-
block">Send Password Reset Link</button>
                    </div>
                    <!-- /.col -->
                </div>
            </form>

            <p class="mt-3 mb-1">
                <a href="{{ route("login") }}">Login</a>
            </p>
            <p class="mb-0">
                <a href="{{ route("register") }}" class="text-center">Register a
new membership</a>
            </p>
        </div>
        <!-- /.login-card-body -->
    </div>
</div>
<!-- /.login-box -->

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

</body>
</html>
```

- **Reset.blade.php**

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <title>{{ config('app.name') }}</title>

    <!-- Tell the browser to be responsive to screen width -->
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport">

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.11.2/css/all.min.css"
          integrity="sha512-
0S+nbAYis87iX26mmj/+fWt1MmaKCv80H+Mbo+Ne7ES4I6rxswpfnC6PxmLiw33Ywj2ghbtTw0FkLbMW
qh4F7Q=="
          crossorigin="anonymous"/>

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <!-- HTML5 Shim and Respond.js IE8 support of HTML5 elements and media
queries -->
    <!-- WARNING: Respond.js doesn't work if you view the page via file:// -->
    <!--[if lt IE 9]>
    <script
src="https://oss.maxcdn.com/html5shiv/3.7.3/html5shiv.min.js"></script>
    <script src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js"></script>
    <![endif]-->

</head>
<body class="hold-transition login-page">
<div class="login-box">
    <div class="login-logo">
        <a href="{{ url('/home') }}"><b>{{ config('app.name') }}</b></a>
    </div>

    <div class="card">
        <div class="card-body login-card-body">
            <p class="login-box-msg">You are only one step a way from your new
password, recover your password now.</p>
```

```
            <form action="{{ route('password.update') }}" method="POST">
                @csrf

                <input type="hidden" name="token" value="{{ $token }}">

                <div class="input-group mb-3">
                    <input type="email"
                           name="email"
                           value="{{ $email ?? old('email') }}"
                           class="form-control @error('email') is-invalid
@enderror"
                           placeholder="Email">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
envelope"></span></div>
                    </div>
                    @error('email')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="password"
                           name="password"
                           class="form-control @error('password') is-invalid
@enderror"
                           placeholder="Password">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
lock"></span></div>
                    </div>
                    @error('password')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="password"
                           name="password_confirmation"
                           class="form-control"
                           placeholder="Confirm Password">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
lock"></span></div>
                    </div>
                </div>

                <div class="row">
                    <div class="col-12">
                        <button type="submit" class="btn btn-primary btn-
block">Reset Password</button>
                    </div>
                    <!-- /.col -->
                </div>
```

```
            </form>

            <p class="mt-3 mb-1">
                <a href="{{ route('login') }}">Login</a>
            </p>
        </div>
        <!-- /.login-card-body -->
    </div>

</div>

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

</body>
</html>
```

- **Login.blade.php**

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <title>{{ config('app.name') }}</title>

    <!-- Tell the browser to be responsive to screen width -->
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport">

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.11.2/css/all.min.css"
          integrity="sha512-
0S+nbAYis87iX26mmj/+fWt1MmaKCv80H+Mbo+Ne7ES4I6rxswpfnC6PxmLiw33Ywj2ghbtTw0FkLbMW
qh4F7Q=="
          crossorigin="anonymous"/>

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
```

```
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <!-- HTML5 Shim and Respond.js IE8 support of HTML5 elements and media
queries -->
    <!-- WARNING: Respond.js doesn't work if you view the page via file:// -->
    <!--[if lt IE 9]>
    <script
src="https://oss.maxcdn.com/html5shiv/3.7.3/html5shiv.min.js"></script>
    <script src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js"></script>
    <![endif]-->

</head>
<body class="hold-transition login-page">
<div class="login-box">
    <div class="login-logo">
        <a href="{{ url('/home') }}"><b>{{ config('app.name') }}</b></a>
    </div>

    <!-- /.login-logo -->

    <!-- /.login-box-body -->
    <div class="card">
        <div class="card-body login-card-body">
            <p class="login-box-msg">Sign in to start your session</p>

            <form method="post" action="{{ url('/login') }}">
                @csrf

                <div class="input-group mb-3">
                    <input type="email"
                           name="email"
                           value="{{ old('email') }}"
                           placeholder="Email"
                           class="form-control @error('email') is-invalid
@enderror">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
envelope"></span></div>
                    </div>
                    @error('email')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="password"
                           name="password"
                           placeholder="Password"
                           class="form-control @error('password') is-invalid
@enderror">
                    <div class="input-group-append">
                        <div class="input-group-text">
```

```
                            <span class="fas fa-lock"></span>
                        </div>
                    </div>
                    @error('password')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror

                </div>

                <div class="row">
                    <div class="col-8">
                        <div class="icheck-primary">
                            <input type="checkbox" id="remember">
                            <label for="remember">Remember Me</label>
                        </div>
                    </div>

                    <div class="col-4">
                        <button type="submit" class="btn btn-primary btn-
block">Sign In</button>
                    </div>

                </div>
            </form>

            <p class="mb-1">
                <a href="{{ route('password.request') }}">I forgot my
password</a>
            </p>
            <p class="mb-0">
                <a href="{{ route('register') }}" class="text-center">Register a
new membership</a>
            </p>
        </div>
        <!-- /.login-card-body -->
    </div>

</div>
<!-- /.login-box -->

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

</body>
</html>
```

Registrer.blade.php

```
<!DOCTYPE html>
```

```
<html>
<head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <title>{{ config('app.name') }} | Registration Page</title>

    <!-- Tell the browser to be responsive to screen width -->
    <meta content="width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no" name="viewport">

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.11.2/css/all.min.css"
          integrity="sha512-
0S+nbAYis87iX26mmj/+fWt1MmaKCv80H+Mbo+Ne7ES4I6rxswpfnC6PxmLiw33Ywj2ghbtTw0FkLbMW
qh4F7Q=="
          crossorigin="anonymous"/>

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <!-- HTML5 Shim and Respond.js IE8 support of HTML5 elements and media
queries -->
    <!-- WARNING: Respond.js doesn't work if you view the page via file:// -->
    <!--[if lt IE 9]>
    <script
src="https://oss.maxcdn.com/html5shiv/3.7.3/html5shiv.min.js"></script>
    <script src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js"></script>
    <![endif]-->
</head>
<body class="hold-transition register-page">
<div class="register-box">
    <div class="register-logo">
        <a href="{{ url('/home') }}"><b>{{ config('app.name') }}</b></a>
    </div>

    <div class="card">
        <div class="card-body register-card-body">
            <p class="login-box-msg">Register a new membership</p>

            <form method="post" action="{{ route('register') }}">
                @csrf
```

```
                <div class="input-group mb-3">
                    <input type="text"
                           name="name"
                           class="form-control @error('name') is-invalid
@enderror"
                           value="{{ old('name') }}"
                           placeholder="Full name">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
user"></span></div>
                    </div>
                    @error('name')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="email"
                           name="email"
                           value="{{ old('email') }}"
                           class="form-control @error('email') is-invalid
@enderror"
                           placeholder="Email">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
envelope"></span></div>
                    </div>
                    @error('email')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="password"
                           name="password"
                           class="form-control @error('password') is-invalid
@enderror"
                           placeholder="Password">
                    <div class="input-group-append">
                        <div class="input-group-text"><span class="fas fa-
lock"></span></div>
                    </div>
                    @error('password')
                    <span class="error invalid-feedback">{{ $message }}</span>
                    @enderror
                </div>

                <div class="input-group mb-3">
                    <input type="password"
                           name="password_confirmation"
                           class="form-control"
                           placeholder="Retype password">
                    <div class="input-group-append">
```

```
                        <div class="input-group-text"><span class="fas fa-
lock"></span></div>
                    </div>
                </div>

                <div class="row">
                    <div class="col-8">
                        <div class="icheck-primary">
                            <input type="checkbox" id="agreeTerms" name="terms"
value="agree">
                            <label for="agreeTerms">
                                I agree to the <a href="#">terms</a>
                            </label>
                        </div>
                    </div>
                    <!-- /.col -->
                    <div class="col-4">
                        <button type="submit" class="btn btn-primary btn-
block">Register</button>
                    </div>
                    <!-- /.col -->
                </div>
            </form>

            <a href="{{ route('login') }}" class="text-center">I already have a
membership</a>
        </div>
        <!-- /.form-box -->
    </div><!-- /.card -->

    <!-- /.form-box -->
</div>
<!-- /.register-box -->

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

</body>
</html>
```

- **Verify.blade.php**

```
@extends('layouts.app')

@section('content')
    <div class="container">
        <div class="row justify-content-center">
            <div class="col-md-7" style="margin-top: 2%">
                <div class="box">
```

```
                    <h3 class="box-title" style="padding: 2%">Verify Your Email
Address</h3>

                    <div class="box-body">
                        @if (session('resent'))
                            <div class="alert alert-success" role="alert">A
fresh verification link has been sent to
                                your email address
                            </div>
                        @endif
                        <p>Before proceeding, please check your email for a
verification link.If you did not receive
                            the email,</p>
                        <a href="{{ route('verification.resend') }}">click here
to request another'</a>.
                    </div>
                </div>
            </div>
        </div>
    </div>
@endsection
```

3.1.2 LAYOUTS

- **App.blade.php**

```
<!DOCTYPE html>
<html>
<head>
    <meta charset="UTF-8">
    <title>{{ config('app.name') }}</title>
    <meta content='width=device-width, initial-scale=1, maximum-scale=1, user-
scalable=no' name='viewport'>

    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-
awesome/5.14.0/css/all.min.css"
          integrity="sha512-
1PKOgIY59xJ8Co8+NE6FZ+LOAZKjy+KY8iq0G4B3CyeY6wYHN3yt9PW0XpSriVlkMXe40PTKnXrLnZ9+
fkDaog=="
          crossorigin="anonymous"/>

    <link href="https://cdn.jsdelivr.net/gh/gitbrent/bootstrap4-
toggle@3.6.1/css/bootstrap4-toggle.min.css"
          rel="stylesheet">

    <!-- AdminLTE -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/css/adminlte.min.css"
          integrity="sha512-
rVZC4rf0Piwtw/LsgwXxKXzWq3L0P6atiQKBNuXYRbg2FoRbSTIY0k2DxuJcs7dk4e/ShtMzglHKBOJx
W8EQyQ=="
          crossorigin="anonymous"/>

    <!-- iCheck -->
```

```
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/icheck-
bootstrap/3.0.1/icheck-bootstrap.min.css"
          integrity="sha512-
8vq2g5nHE062j3xor4XxPeZiPjmRDh6wlufQlfC6pdQ/9urJkU07NM0tEREeymP++NczacJ/Q59ul+/K
2eYvcg=="
          crossorigin="anonymous"/>

    <link rel="stylesheet"
href="https://cdnjs.cloudflare.com/ajax/libs/select2/4.0.13/css/select2.min.css"
          integrity="sha512-
nMNlpuaDPrqlEls3IX/Q56H36qvBASwb3ipuo3MxeWbsQB1881ox0cRv7UPTgBlriqoynt35KjEwgGUe
UXIPnw=="
          crossorigin="anonymous"/>

    <link rel="stylesheet"
          href="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-
datetimepicker/4.17.47/css/bootstrap-datetimepicker.min.css"
          integrity="sha512-
aEe/ZxePawj0+G2R+AaIxgrQuKT68I28qh+wgLrcAJOz3rxCP+TwrK5SPN+E5I+1IQjNtcfvb96HDagw
rKRdBw=="
          crossorigin="anonymous"/>

    @yield('third_party_stylesheets')

    @stack('page_css')
</head>

<body class="hold-transition sidebar-mini layout-fixed">
<div class="wrapper">
    <!-- Main Header -->
    <nav class="main-header navbar navbar-expand navbar-white navbar-light">
        <!-- Left navbar links -->
        <ul class="navbar-nav">
            <li class="nav-item">
                <a class="nav-link" data-widget="pushmenu" href="#"
role="button"><i class="fas fa-bars"></i></a>
            </li>
        </ul>

        <ul class="navbar-nav ml-auto">
            <li class="nav-item dropdown user-menu">
                <a href="#" class="nav-link dropdown-toggle" data-
toggle="dropdown">
                    <img src="{{asset('img/DeusTerra.png')}}"
                         class="user-image img-circle elevation-2" alt="User
Image">
                    <span class="d-none d-md-inline">{{ Auth::user()->name
}}</span>
                </a>
                <ul class="dropdown-menu dropdown-menu-lg dropdown-menu-right">
                    <!-- User image -->
                    <li class="user-header bg-primary">
                        <img src="{{asset('img/DeusTerra.png')}}"
                             class="img-circle elevation-2"
                             alt="User Image">
```

```
                        <p>
                            {{ Auth::user()->name }}
                            <small>Member since {{ Auth::user()->created_at-
>format('M. Y') }}</small>
                        </p>
                    </li>
                    <!-- Menu Footer-->
                    <li class="user-footer">
                        <a href="#" class="btn btn-default btn-flat">Profile</a>
                        <a href="#" class="btn btn-default btn-flat float-right"
                           onclick="event.preventDefault();
document.getElementById('logout-form').submit();">
                            Sign out
                        </a>
                        <form id="logout-form" action="{{ route('logout') }}"
method="POST" class="d-none">
                            @csrf
                        </form>
                    </li>
                </ul>
            </li>
        </ul>
    </nav>

    <!-- Left side column. contains the logo and sidebar -->
@include('layouts.sidebar')

<!-- Content Wrapper. Contains page content -->
    <div class="content-wrapper">
        <section class="content">
            @yield('content')
        </section>
    </div>

    <!-- Main Footer -->
    <footer class="main-footer">
        <div class="float-right d-none d-sm-block">
            <b>Version</b> 3.0.5
        </div>
        <strong>Copyright &copy; 2014-2020 <a
href="https://adminlte.io">AdminLTE.io</a>.</strong> All rights
        reserved.
    </footer>
</div>

<script src="https://cdnjs.cloudflare.com/ajax/libs/jquery/3.5.1/jquery.min.js"
        integrity="sha512-
bLT0Qm9VnAYZDflyKcBaQ2gg0hSYNQrJ8RilYldYQ1FxQYoCLtUjuuRuZo+fjqhx/qtq/1itJ0C2ejDx
ltZVFg=="
        crossorigin="anonymous"></script>

<script
src="https://cdn.jsdelivr.net/npm/popper.js@1.16.1/dist/umd/popper.min.js"
        integrity="sha384-
9/reFTGAW83EW2RDu2S0VKaIzap3H66lZH81PoYlFhbGU+6BZp6G7niu735Sk7lN"
```

```
        crossorigin="anonymous"></script>

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@4.5.3/dist/js/bootstrap.min.js"
        integrity="sha384-
w1Q4orYjBQndcko6MimVbzY0tgp4pWB4lZ7lr30WKz0vr/aWKhXdBNmNb5D92v7s"
        crossorigin="anonymous"></script>

<script src="https://cdn.jsdelivr.net/npm/bs-custom-file-input/dist/bs-custom-
file-input.min.js"></script>

<!-- AdminLTE App -->
<script src="https://cdnjs.cloudflare.com/ajax/libs/admin-
lte/3.0.5/js/adminlte.min.js"
        integrity="sha512-
++c7zGcm18AhH83pOIETVReg0dr1Yn8XTRw+0bWSIWAVCAwz1s2PwnSj4z/OOyKlwSXc4RLg3nnjR22q
0dhEyA=="
        crossorigin="anonymous"></script>

<script
src="https://cdnjs.cloudflare.com/ajax/libs/moment.js/2.27.0/moment.min.js"
        integrity="sha512-
rmZcZsyhe0/MAjquhTgiUcb4d9knaFc7b5xAfju483gbEXTkeJRUMIPk6s3ySZMYUHEcjKbjLjyddGWM
rNEvZg=="
        crossorigin="anonymous"></script>

<script src="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-
datetimepicker/4.17.47/js/bootstrap-datetimepicker.min.js"
        integrity="sha512-
GDey37RZAxFkpFeJorEUwNoIbkTwsyC736KNSYucu1WJWFK9qTdzYub8ATxktr6Dwke7nbFaioypzbDO
QykoRg=="
        crossorigin="anonymous"></script>

<script src="https://cdn.jsdelivr.net/gh/gitbrent/bootstrap4-
toggle@3.6.1/js/bootstrap4-toggle.min.js"></script>

<script
src="https://cdnjs.cloudflare.com/ajax/libs/select2/4.0.13/js/select2.min.js"
        integrity="sha512-
2ImtlRlf2VVmiGZsjm9bEyhjGW4dU7B6TNwh/hx/iSByxNENtj3WVE6o/9Lj4TJeVXPi4bnOIMXFIJJA
eufa0A=="
        crossorigin="anonymous"></script>

<script src="https://cdnjs.cloudflare.com/ajax/libs/bootstrap-
switch/3.3.4/js/bootstrap-switch.min.js" integrity="sha512-
J+763o/bd3r9iW+gFEqTaeyi+uAphmzkE/zU8FxY6iAvD3nQKXa+ZAWkBI9QS9QkYEKddQoiy0I5GDxK
f/ORBA==" crossorigin="anonymous"></script>

<script>
    $(function () {
        bsCustomFileInput.init();
    });

    $("input[data-bootstrap-switch]").each(function(){
        $(this).bootstrapSwitch('state', $(this).prop('checked'));
```

```
    });
</script>

@stack('third_party_scripts')

@stack('page_scripts')
</body>
</html>
```

- **Datatables_Css.blade.php**

```
<!-- DataTable Bootstrap -->
<!-- <link
href="https://cdn.datatables.net/1.10.21/css/dataTables.bootstrap.min.css"
rel="stylesheet">
<link rel="stylesheet"
href="https://cdn.datatables.net/buttons/1.6.2/css/buttons.bootstrap4.min.css">
 -->

<link href="https://cdnjs.cloudflare.com/ajax/libs/twitter-
bootstrap/4.5.2/css/bootstrap.css" rel="stylesheet" defer>
<link rel="stylesheet"
href="https://cdn.datatables.net/1.10.23/css/dataTables.bootstrap4.min.css"
defer>
<link rel="stylesheet"
href="https://cdn.datatables.net/buttons/1.6.5/css/buttons.bootstrap4.min.css"
defer>
```

- **Datatables_js.blade.php**

```
<!-- Datatables -->
<script src="https://cdn.datatables.net/1.10.21/js/jquery.dataTables.min.js"
defer></script>
<script src="https://cdn.datatables.net/1.10.21/js/dataTables.bootstrap4.min.js"
defer></script>
<script
src="https://cdn.datatables.net/buttons/1.6.2/js/dataTables.buttons.min.js"
defer></script>
<script
src="https://cdn.datatables.net/buttons/1.6.2/js/buttons.bootstrap4.min.js"
defer></script>
<script src="https://cdn.datatables.net/buttons/1.6.2/js/buttons.colVis.min.js"
defer></script>
<script src="{{ asset('vendor/datatables/buttons.server-side.js') }}"
defer></script>
```

- **Menu.blade.php**

```
<li class="nav-item">
    <a href="{{ route('projects.index') }}"
       class="nav-link {{ Request::is('projects*') ? 'active' : '' }}">
        <p>Projects</p>
```

```
    </a>
</li>
```

- **Sidebar.blade.php**

```
<aside class="main-sidebar sidebar-dark-primary elevation-4">
    <a href="{{ route('home') }}" class="brand-link">
        <img src="{{asset('img/DeusTerra.png')}}"
             alt="{{ config('app.name') }} Logo"
             class="brand-image img-circle elevation-3">
        <span class="brand-text font-weight-light">{{ config('app.name')
}}</span>
    </a>

    <div class="sidebar">
        <nav class="mt-2">
            <ul class="nav nav-pills nav-sidebar flex-column" data-
widget="treeview" role="menu" data-accordion="false">
                @include('layouts.menu')
            </ul>
        </nav>
    </div>

</aside>
```

3.1.3 PROJECTS

- **create.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-12">
                    <h1>Create Project</h1>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">

        @include('adminlte-templates::common.errors')

        <div class="card">

            {!! Form::open(['route' => 'projects.store', 'files' => true]) !!}

            <div class="card-body">
```

```
                <div class="row">
                    @include('projects.fields')
                </div>

            </div>

            <div class="card-footer">
                {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
                <a href="{{ route('projects.index') }}" class="btn btn-
default">Cancel</a>
            </div>

            {!! Form::close() !!}

        </div>
    </div>
@endsection
```

- **datatables_actions.blade.php**

```
{!! Form::open(['route' => ['projects.destroy', $id], 'method' => 'delete']) !!}
<div class='btn-group'>
    <a href="{{ route('properties.index', $id) }}" class='btn btn-success btn-
xs'>
        <i class="fa fa-list fa-xs"></i>
    </a>
    <a href="{{ route('projects.show', $id) }}" class='btn btn-default btn-xs'>
        <i class="fa fa-eye fa-xs"></i>
    </a>
    <a href="{{ route('projects.edit', $id) }}" class='btn btn-default btn-xs'>
        <i class="fa fa-edit fa-xs"></i>
    </a>
    {!! Form::button('<i class="fa fa-trash fa-xs"></i>', [
        'type' => 'submit',
        'class' => 'btn btn-danger btn-xs',
        'onclick' => "return confirm('Are you sure?')"
    ]) !!}
</div>
{!! Form::close() !!}
```

- **edit.table.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-12">
                    <h1>Edit Project</h1>
                </div>
```

```
            </div>
        </div>
    </section>

    <div class="content px-3">

        @include('adminlte-templates::common.errors')

        <div class="card">

            {!! Form::model($project, ['route' => ['projects.update', $project-
>id], 'method' => 'patch', 'files' => true]) !!}

            <div class="card-body">
                <div class="row">
                    @include('projects.fields')
                </div>
            </div>

            <div class="card-footer">
                {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
                <a href="{{ route('projects.index') }}" class="btn btn-
default">Cancel</a>
            </div>

           {!! Form::close() !!}

        </div>
    </div>
@endsection
```

- **fields.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-6">
                    <h1>Projects</h1>
                </div>
                <div class="col-sm-6">
                    <a class="btn btn-primary float-right"
                       href="{{ route('projects.create') }}">
                        Add New
                    </a>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">
```

```
        @include('flash::message')

        <div class="clearfix"></div>

        <div class="card">
            <div class="card-body p-2">
                @include('projects.table')

                <div class="card-footer clearfix float-right">
                    <div class="float-right">

                    </div>
                </div>
            </div>

        </div>
    </div>

@endsection
```

- **index.blade.php**

```
<!-- Name Field -->
<div class="col-sm-12">
    {!! Form::label('name', 'Name:') !!}
    <p>{{ $project->name }}</p>
</div>

<!-- Responsible Field -->
<div class="col-sm-12">
    {!! Form::label('responsible', 'Responsible:') !!}
    <p>{{ $project->responsible }}</p>
</div>

<!-- Pdt Field -->
<div class="col-sm-12">
    {!! Form::label('pdt', 'Pdt:') !!}
    <p>
    <a class="btn btn-info ml-2 col-md-4" href="{{ url(Storage::url($project-
>pdt))}}" target="_blank">
        Download <i class="fa fa-download"></i>
    </a>
    </p>
</div>

<!-- Status Field -->
<div class="col-sm-12">
    {!! Form::label('status', 'Status:') !!}
    <p>{{ $project->status }}</p>
</div>

<!-- View Properties -->
<div class="col-sm-12">
```

```
    {!! Form::label('properties', 'Properties:') !!}
    <p>
    <a href="{{ route('properties.index', $project->id) }}" class='btn btn-
success col-md-4'>
        View Properties <i class="fa fa-list"></i>
    </a>
    </p>
</div>

<!-- Created At Field -->
<div class="col-sm-12">
    {!! Form::label('created_at', 'Created At:') !!}
    <p>{{ $project->created_at }}</p>
</div>

<!-- Updated At Field -->
<div class="col-sm-12">
    {!! Form::label('updated_at', 'Updated At:') !!}
    <p>{{ $project->updated_at }}</p>
</div>
```

- **show_fields.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-6">
                    <h1>Project Details</h1>
                </div>
                <div class="col-sm-6">
                    <a class="btn btn-default float-right"
                       href="{{ route('projects.index') }}">
                        Back
                    </a>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">
        <div class="card">

            <div class="card-body">
                <div class="row">
                    @include('projects.show_fields')
                </div>
            </div>

        </div>
    </div>
```

```
@endsection
```

- **show.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-6">
                    <h1>Project Details</h1>
                </div>
                <div class="col-sm-6">
                    <a class="btn btn-default float-right"
                       href="{{ route('projects.index') }}">
                        Back
                    </a>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">
        <div class="card">

            <div class="card-body">
                <div class="row">
                    @include('projects.show_fields')
                </div>
            </div>

        </div>
    </div>
@endsection
```

- **table.blade.php**

```
@section('third_party_stylesheets')
    @include('layouts.datatables_css')
@endsection

{!! $dataTable->table(['width' => '100%', 'class' => 'table table-striped table-
bordered']) !!}

@push('third_party_scripts')
    @include('layouts.datatables_js')
    {!! $dataTable->scripts() !!}
@endpush
```

3.1.3 PROPERTIES

- **Act_modal.blade.php**

```
@php
use App\Http\Controllers\Custom\CurrencyHelpers;
@endphp
<div id="actModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Act</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- act_value Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('act_value', 'Act Value:') !!}
              {{CurrencyHelpers::numberToCurrency($property->act_value)}}
              {!! Form::number('act_value', null, ['class' => 'form-control',
'required' => true]) !!}
          </div>
          <!-- act_payment_date Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('act_payment_date', 'Act Payment Date:') !!}
              {{substr($property->act_payment_date, 0,10)}}
              {!! Form::date('act_payment_date', null, ['class' => 'form-
control', 'required' => true]) !!}
          </div>
          <!-- act Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('act', 'Act:') !!}
              {{substr($property->act_date, 0,10)}}
              @if(isset($property->act))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->act)) }}" target="_blank">
                  Download Act <i class="fa fa-download"></i>
              </a>
              </p>
              @endif
              <div class="input-group">
                  <div class="custom-file">
                      {!! Form::file('act', ['class' => 'custom-file-input'])
!!}
                      {!! Form::label('act', $property->act ? 'Change file' :
'Choose file', ['class' => 'custom-file-label']) !!}
                  </div>
              </div>
          </div>
          <!-- act_payment Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('act_payment', 'Act Payment:') !!}
              @if(isset($property->act_payment))
```

```
                <p>
                <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->act_payment)) }}" target="_blank">
                    Download Act Payment <i class="fa fa-download"></i>
                </a>
                </p>
                @endif
                <div class="input-group">
                    <div class="custom-file">
                        {!! Form::file('act_payment', ['class' => 'custom-file-
input']) !!}
                        {!! Form::label('act_payment', $property->act_payment ?
'Change file' : 'Choose file', ['class' => 'custom-file-label']) !!}
                    </div>
                </div>
            </div>
            <div class="clearfix"></div>
        </div>
        <div class="modal-footer">
          {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
          <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
        </div>
      {!! Form::close() !!}
    </div>
  </div>
</div>
```

- **create.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-12">
                    <h1>Create Property</h1>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">

        @include('adminlte-templates::common.errors')

        <div class="card">

            {!! Form::open(['route' => 'properties.store', 'files' => true]) !!}

            <div class="card-body">

                <div class="row">
                    @include('properties.fields')
```

```
                </div>

            </div>

            <div class="card-footer">
                {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
                <a href="{{ route('properties.index', $project) }}" class="btn
btn-default">Cancel</a>
            </div>

            {!! Form::close() !!}

        </div>
    </div>
@endsection
```

- **datatables_actions.blade.php**

```
{!! Form::open(['route' => ['properties.destroy', $id], 'method' => 'delete'])
!!}
<div class='btn-group'>
    <a href="{{ route('properties.show', $id) }}" class='btn btn-default btn-
xs'>
        <i class="fa fa-eye fa-xs"></i>
    </a>
    <a href="{{ route('properties.edit', $id) }}" class='btn btn-default btn-
xs'>
        <i class="fa fa-edit fa-xs"></i>
    </a>
    {!! Form::button('<i class="fa fa-trash fa-xs"></i>', [
        'type' => 'submit',
        'class' => 'btn btn-danger btn-xs',
        'onclick' => "return confirm('Are you sure?')"
    ]) !!}
</div>
{!! Form::close() !!}
```

- **easement_modal.blade.php**

```
@php
use App\Http\Controllers\Custom\CurrencyHelpers;
@endphp
<div id="easementModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Easement</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
```

```
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- easement_value Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('easement_value', 'Easement Value:') !!}
              {{CurrencyHelpers::numberToCurrency($property->easement_value)}}
              {!! Form::number('easement_value', null, ['class' => 'form-
control', 'required' => true]) !!}
          </div>
          <!-- easement_payment_date Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('easement_payment_date', 'Easement Payment Date:')
!!}
              {{substr($property->easement_payment_date, 0,10)}}
              {!! Form::date('easement_payment_date', null, ['class' => 'form-
control', 'required' => true]) !!}
          </div>
          <!-- Easement Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('easement', 'Easement:') !!}
              {{substr($property->easement_date, 0,10)}}
              @if(isset($property->easement))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->easement)) }}" target="_blank">
                  Download Easement <i class="fa fa-download"></i>
              </a>
              </p>
              @endif
              <div class="input-group">
                  <div class="custom-file">
                      {!! Form::file('easement', ['class' => 'custom-file-
input']) !!}
                      {!! Form::label('easement', $property->easement ? 'Change
file' : 'Choose file', ['class' => 'custom-file-label']) !!}
                  </div>
              </div>
          </div>
          <!-- easement_payment Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('easement_payment', 'Easement Payment:') !!}
              @if(isset($property->easement_payment))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->easement_payment)) }}" target="_blank">
                  Download Easement Payment <i class="fa fa-download"></i>
              </a>
              </p>
              @endif
              <div class="input-group">
                  <div class="custom-file">
                      {!! Form::file('easement_payment', ['class' => 'custom-
file-input']) !!}
```

```
                    {!! Form::label('easement_payment', $property-
>easement_payment ? 'Change file' : 'Choose file', ['class' => 'custom-file-
label']) !!}
                </div>
              </div>
          </div>
          <div class="clearfix"></div>
        </div>
        <div class="modal-footer">
          {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
          <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
        </div>
      {!! Form::close() !!}
    </div>
  </div>
</div>
```

edit.blade.php

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-12">
                    <h1>Edit Property</h1>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">

        @include('adminlte-templates::common.errors')

        <div class="card">

            {!! Form::model($property, ['route' => ['properties.update',
$property->id], 'method' => 'patch', 'files' => true]) !!}

            <div class="card-body">
                <div class="row">
                    @include('properties.fields')
                </div>
            </div>

            <div class="card-footer">
                {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
                <a href="{{ route('properties.index', $property->project) }}"
class="btn btn-default">Cancel</a>
            </div>

           {!! Form::close() !!}
```

```
        </div>
    </div>
@endsection
```

- **fields.blade.php**

```
<!-- Name Field -->
<div class="form-group col-sm-6">
    {!! Form::label('name', 'Name:') !!}
    {!! Form::text('name', null, ['class' => 'form-control']) !!}
</div>

<!-- Project Field -->
    {!! Form::hidden('project', isset($project) ? $project : $property->project,
['class' => 'form-control']) !!}

<!-- Idsig Field -->
<div class="form-group col-sm-6">
    {!! Form::label('idsig', 'Idsig:') !!}
    {!! Form::text('idsig', null, ['class' => 'form-control']) !!}
</div>

<!-- Field Report Field -->
<div class="form-group col-sm-6">
    {!! Form::label('field_report', 'Field Report:') !!}
    <div class="input-group">
        <div class="custom-file">
            {!! Form::file('field_report', ['class' => 'custom-file-input']) !!}
            {!! Form::label('field_report', 'Choose file', ['class' => 'custom-
file-label']) !!}
        </div>
    </div>
</div>
<div class="clearfix"></div>


<!-- Map Field -->
<div class="form-group col-sm-6">
    {!! Form::label('map', 'Map:') !!}
    <div class="input-group">
        <div class="custom-file">
            {!! Form::file('map', ['class' => 'custom-file-input']) !!}
            {!! Form::label('map', 'Choose file', ['class' => 'custom-file-
label']) !!}
        </div>
    </div>
</div>
<div class="clearfix"></div>


<!-- Status Field -->
<div class="form-group col-sm-6">
```

```
    {!! Form::label('status', 'Status:') !!}
    {!! Form::select('status', ['En Gestión' => 'En Gestión', 'Anulado' =>
'Anulado', 'Finalizado' => 'Finalizado'], null, ['class' => 'form-control
custom-select']) !!}
</div>
```

- **imposition_modal.blade.php**

```
@php
use App\Http\Controllers\Custom\CurrencyHelpers;
@endphp
<div id="impositionModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Imposition</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- imposition_value Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('imposition_value', 'Imposition Value:') !!}
              {{CurrencyHelpers::numberToCurrency($property->imposition_value)}}
              {!! Form::number('imposition_value', null, ['class' => 'form-
control', 'required' => true]) !!}
          </div>
          <!-- imposition_payment_date Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('imposition_payment_date', 'Imposition Payment
Date:') !!}
              {{substr($property->imposition_payment_date, 0,10)}}
              {!! Form::date('imposition_payment_date', null, ['class' => 'form-
control', 'required' => true]) !!}
          </div>
          <!-- Imposition Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('imposition', 'Imposition:') !!}
              {{substr($property->imposition_date, 0,10)}}
              @if(isset($property->imposition))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->imposition)) }}" target="_blank">
                  Download Imposition <i class="fa fa-download"></i>
              </a>
              </p>
              @endif
              <div class="input-group">
                  <div class="custom-file">
```

```
                    {!! Form::file('imposition', ['class' => 'custom-file-
input']) !!}
                    {!! Form::label('imposition', $property->Imposition ?
'Change file' : 'Choose file', ['class' => 'custom-file-label']) !!}
                </div>
            </div>
        </div>
        <!-- imposition_payment Field -->
        <div class="form-group col-sm-12">
            {!! Form::label('imposition_payment', 'Imposition Payment:') !!}
            @if(isset($property->imposition_payment))
            <p>
            <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->imposition_payment)) }}" target="_blank">
                Download Imposition Payment <i class="fa fa-download"></i>
            </a>
            </p>
            @endif
            <div class="input-group">
                <div class="custom-file">
                    {!! Form::file('imposition_payment', ['class' => 'custom-
file-input']) !!}
                    {!! Form::label('imposition_payment', $property-
>imposition_payment ? 'Change file' : 'Choose file', ['class' => 'custom-file-
label']) !!}
                </div>
            </div>
        </div>
        <div class="clearfix"></div>
      </div>
      <div class="modal-footer">
        {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
        <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
      </div>
    {!! Form::close() !!}
  </div>
</div>
</div>
```

- **index.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-6">
                    <h1>Properties</h1>
                </div>
                <div class="col-sm-6">
                    <a class="btn btn-primary float-right"
                       href="{{ route('properties.create', $project) }}">
                        Add New
```

```
                    </a>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">

        @include('flash::message')

        <div class="clearfix"></div>

        <div class="card">
            <div class="card-body p-2">
                @include('properties.table')

                <div class="card-footer clearfix float-right">
                    <div class="float-right">

                    </div>
                </div>
            </div>

        </div>
    </div>

@endsection
```

- **inventory_modal.blade.php**

```
<div id="inventoryModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Inventory</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- inventory Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('inventory', 'Inventory:') !!}
              {{substr($property->inventory_date, 0,10)}}
              @if(isset($property->inventory))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->inventory)) }}" target="_blank">
                  Download inventory <i class="fa fa-download"></i>
              </a>
```

```
            </p>
            @endif
            <div class="input-group">
                <div class="custom-file">
                    {!! Form::file('inventory', ['class' => 'custom-file-
input']) !!}
                    {!! Form::label('inventory', $property->inventory ?
'Change file' : 'Choose file', ['class' => 'custom-file-label']) !!}
                </div>
            </div>
          </div>
          <div class="clearfix"></div>
        </div>
        <div class="modal-footer">
          {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
          <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
        </div>
      {!! Form::close() !!}
    </div>
  </div>
</div>
```

- **show_fields.blade.php**

```
<!-- Name Field -->
<div class="col-sm-6">
    {!! Form::label('name', 'Name:') !!}
    <p>{{ $property->name }}</p>
</div>

<!-- Project Field -->
<div class="col-sm-6">
    {!! Form::label('project', 'Project:') !!}
    <p>{{ $property->associated_project->name }}</p>
</div>

<!-- Idsig Field -->
<div class="col-sm-6">
    {!! Form::label('idsig', 'Idsig:') !!}
    <p>{{ $property->idsig }}</p>
</div>

<!-- Status Field -->
<div class="col-sm-6">
    {!! Form::label('status', 'Status:') !!}
    <p>{{ $property->status }}</p>
</div>

<!-- Field Report Field -->
<div class="col-sm-6">
    {!! Form::label('field_report', 'Field Report:') !!}
    <p>
    <a class="btn btn-default ml-2 col-md-6" href="{{
url(Storage::url($property->field_report)) }}" target="_blank">
```

```
        Download <i class="fa fa-download"></i>
    </a>
    </p>
</div>

<!-- Map Field -->
<div class="col-sm-6">
    {!! Form::label('map', 'Map:') !!}
    <p>
    <a class="btn btn-default ml-2 col-md-6" href="{{
url(Storage::url($property->map)) }}" target="_blank">
        Download <i class="fa fa-download"></i>
    </a>
    </p>
</div>

<!-- Created At Field -->
<div class="col-sm-6">
    {!! Form::label('created_at', 'Created At:') !!}
    <p>{{ $property->created_at }}</p>
</div>

<!-- Updated At Field -->
<div class="col-sm-6">
    {!! Form::label('updated_at', 'Updated At:') !!}
    <p>{{ $property->updated_at }}</p>
</div>

<div class="clearfix"></div>

<hr style="width:100%;text-align:left;margin-left:0"></hr>
<hr style="width:100%;text-align:left;margin-left:0"></hr>

<!-- Documents Field -->


<div class="col-sm-12 text-center">
    {!! Form::label('documents', 'Documents:') !!}


    <!-- Study Modal -->
    <p>
    <a class="btn {{$property->study ? 'btn-success' : 'btn-warning'}} ml-2 col-
md-4" data-toggle="modal" data-target="#studyModal">
        Legal Study <i class="fa fa-book"></i>
    </a>
    @include('properties.study_modal')
    </p>

    <!-- WorkAd Modal -->
    <p>
    <a class="btn {{$property->workad ? 'btn-success' : 'btn-warning'}} ml-2
col-md-4" data-toggle="modal" data-target="#workadModal">
        Work Ad <i class="fa fa-book"></i>
    </a>
```

```
    @include('properties.workad_modal')
    </p>

    <!-- Inventory Modal -->
    <p>
    <a class="btn {{$property->inventory ? 'btn-success' : 'btn-warning'}} ml-2
col-md-4" data-toggle="modal" data-target="#inventoryModal">
        Inventory <i class="fa fa-book"></i>
    </a>
    @include('properties.inventory_modal')
    </p>

    <!-- Act Modal -->
    <p>
    <a class="btn {{$property->act ? 'btn-success' : 'btn-warning'}} ml-2 col-
md-4" data-toggle="modal" data-target="#actModal">
        Act <i class="fa fa-book"></i>
    </a>
    @include('properties.act_modal')
    </p>

    <!-- Easement Modal -->
    <p>
    <a class="btn {{$property->easement ? 'btn-success' : 'btn-warning'}} ml-2
col-md-4" data-toggle="modal" data-target="#easementModal">
        Easement <i class="fa fa-book"></i>
    </a>
    @include('properties.easement_modal')
    </p>

    <!-- Imposition Modal -->
    <p>
    <a class="btn {{$property->imposition ? 'btn-success' : 'btn-warning'}} ml-2
col-md-4" data-toggle="modal" data-target="#impositionModal">
        Imposition <i class="fa fa-book"></i>
    </a>
    @include('properties.imposition_modal')
    </p>
</div>
```

- **show.blade.php**

```
@extends('layouts.app')

@section('content')
    <section class="content-header">
        <div class="container-fluid">
            <div class="row mb-2">
                <div class="col-sm-6">
                    <h1>Property Details</h1>
                </div>
                <div class="col-sm-6">
                    <a class="btn btn-default float-right"
```

```
                        href="{{ route('properties.index', $property->project)
}}">
                         Back
                    </a>
                </div>
            </div>
        </div>
    </section>

    <div class="content px-3">

    @include('adminlte-templates::common.errors')

        <div class="card">

            <div class="card-body">
                <div class="row">
                    @include('properties.show_fields')
                </div>
            </div>

        </div>
    </div>
@endsection
```

- **study_modal.php**

```
<div id="studyModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Legal Study</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- Viability Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('viability', 'Viability:') !!}
              {!! Form::select('viability', ['' => 'Seleccionar', 'Viable' =>
'Viable', 'No viable' => 'No viable', 'Condicionado' => 'Condicionado'], null,
['class' => 'form-control custom-select', 'required' => true]) !!}
          </div>
          <!-- study Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('study', 'Study:') !!}
              {{substr($property->study_date, 0,10)}}
              @if(isset($property->study))
              <p>
```

```
            <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->study)) }}" target="_blank">
                Download study <i class="fa fa-download"></i>
            </a>
            </p>
            @endif
            <div class="input-group">
                <div class="custom-file">
                    {!! Form::file('study', ['class' => 'custom-file-input'])
!!}
                    {!! Form::label('study', $property->study ? 'Change file'
: 'Choose file', ['class' => 'custom-file-label']) !!}
                </div>
            </div>
          </div>
          <div class="clearfix"></div>
        </div>
        <div class="modal-footer">
          {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
          <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
        </div>
      {!! Form::close() !!}
    </div>
  </div>
</div>
```

- **table.blade.php**

```
@section('third_party_stylesheets')
    @include('layouts.datatables_css')
@endsection

{!! $dataTable->table(['width' => '100%', 'class' => 'table table-striped table-
bordered']) !!}

@push('third_party_scripts')
    @include('layouts.datatables_js')
    {!! $dataTable->scripts() !!}
@endpush
```

- **workad_modal.php**

```
<div id="workadModal" class="modal" tabindex="-1" role="dialog">
  <div class="modal-dialog" role="document">
    <div class="modal-content">
      <div class="modal-header">
        <h5 class="modal-title">Work Ad</h5>
        <button type="button" class="close" data-dismiss="modal" aria-
label="Close">
          <span aria-hidden="true">&times;</span>
        </button>
      </div>
```

```
      {!! Form::model($property, ['route' => ['properties.add.documents',
$property->id], 'method' => 'patch', 'files' => true]) !!}
        <div class="modal-body">
          <!-- direct_agreement Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('direct_agreement', 'Direct Agreement:') !!}
              {!! Form::select('direct_agreement', ['' => 'Seleccionar',
'Acuerdo Directo' => 'Acuerdo Directo', 'Imposición' => 'Imposición'], null,
['class' => 'form-control custom-select', 'required' => true]) !!}
          </div>
          <!-- workad Field -->
          <div class="form-group col-sm-12">
              {!! Form::label('workad', 'Work Ad:') !!}
              {{substr($property->workad_date, 0,10)}}
              @if(isset($property->workad))
              <p>
              <a class="btn btn-info ml-2 col-sm-8" href="{{
url(Storage::url($property->workad)) }}" target="_blank">
                  Download workad <i class="fa fa-download"></i>
              </a>
              </p>
              @endif
              <div class="input-group">
                  <div class="custom-file">
                      {!! Form::file('workad', ['class' => 'custom-file-input'])
!!}
                      {!! Form::label('workad', $property->workad ? 'Change
file' : 'Choose file', ['class' => 'custom-file-label']) !!}
                  </div>
              </div>
          </div>
          <div class="clearfix"></div>
        </div>
        <div class="modal-footer">
          {!! Form::submit('Save', ['class' => 'btn btn-primary']) !!}
          <button type="button" class="btn btn-secondary" data-
dismiss="modal">Close</button>
        </div>
      {!! Form::close() !!}
    </div>
  </div>
</div>
```

3.1.4 VENDOR / DATATABLES

- **Editor.blade.php**

```
$(function(){
    window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} =
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} || {};
    $.ajaxSetup({headers: {'X-CSRF-TOKEN': '{{csrf_token()}}'}});
    @foreach($editors as $editor)
        var {{$editor->instance}} = window.{{ config('datatables-
html.namespace', 'LaravelDataTables') }}["%1$s-{{$editor->instance}}"] = new
$.fn.dataTable.Editor({!! $editor->toJson() !!});
```

```
        {!! $editor->scripts  !!}
        @foreach ((array) $editor->events as $event)
            {{$editor->instance}}.on('{!! $event['event']  !!}', {!!
$event['script'] !!});
        @endforeach
    @endforeach
    window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}["%1$s"] = $("#%1$s").DataTable(%2$s);
});
```

- **Funtion.blade.php**

```
window.dtx = window.dtx || {};
window.dtx["%1$s"] = function(opts) {
    window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} =
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} || {};
    @if(isset($editors))
    @foreach($editors as $editor)
        var {{$editor->instance}} = window.{{ config('datatables-
html.namespace', 'LaravelDataTables') }}["%1$s-{{$editor->instance}}"] = new
$.fn.dataTable.Editor({!! $editor->toJson() !!});
        {!! $editor->scripts  !!}
        @foreach ((array) $editor->events as $event)
            {{$editor->instance}}.on('{!! $event['event']  !!}', {!!
$event['script'] !!});
        @endforeach
    @endforeach
    @endif
    return window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}["%1$s"] = $("#%1$s").DataTable($.extend(%2$s, opts));
}
```

- **Options.blade.php**

```
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} =
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }} || {};
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }}.options =
%2$s
window.{{ config('datatables-html.namespace', 'LaravelDataTables') }}.editors =
[];
@foreach($editors as $editor)
window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}.editors["{{$editor->instance}}"] = {!! $editor->toJson()  !!}
@endforeach
```

- **Print.blade.php**

```
<!DOCTYPE html>
<html lang="en">
    <head>
        <title>Print Table</title>
        <meta charset="UTF-8">
        <meta name=description content="">
```

```
        <meta name="viewport" content="width=device-width, initial-scale=1.0">
        <!-- Bootstrap CSS -->
        <link
href="https://maxcdn.bootstrapcdn.com/bootstrap/3.3.5/css/bootstrap.min.css"
rel="stylesheet">
        <link rel="stylesheet" href="https://maxcdn.bootstrapcdn.com/font-
awesome/4.4.0/css/font-awesome.min.css">
        <style>
            body {margin: 20px}
        </style>
    </head>
    <body>
        <table class="table table-bordered table-condensed table-striped">
            @foreach($data as $row)
                @if ($loop->first)
                    <tr>
                        @foreach($row as $key => $value)
                            <th>{!! $key !!}</th>
                        @endforeach
                    </tr>
                @endif
                <tr>
                    @foreach($row as $key => $value)
                        @if(is_string($value) || is_numeric($value))
                            <td>{!! $value !!}</td>
                        @else
                            <td></td>
                        @endif
                    @endforeach
                </tr>
            @endforeach
        </table>
    </body>
</html>
```

- **Script.blade.php**

```
$(function(){window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}=window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}||{};window.{{ config('datatables-html.namespace', 'LaravelDataTables')
}}["%1$s"]=$("#%1$s").DataTable(%2$s);});
```

- **home.blade.php**

```
@extends('layouts.app')

@section('content')
<div class="container">

    <div class="row">
    <div class="max-w-6xl mx-auto sm:px-6 lg:px-8 text-center p-4">
    <img src="{{asset('img/DeusTerra.png')}}"
```

```
                            class="img-circle"
                            alt="Deus Terra">
    <h1 style="color: #aaaaaa">DeusTerra</h1>
    </div>

    </div>
</div>
@endsection
```

- **Welcome.blade.php.**

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
<head>
    <meta charset="utf-8">
    <meta name="viewport" content="width=device-width, initial-scale=1">

    <title>Laravel</title>

    <!-- Fonts -->
    <link
href="https://fonts.googleapis.com/css2?family=Nunito:wght@400;600;700&display=s
wap" rel="stylesheet">
    <link href="https://cdn.jsdelivr.net/gh/gitbrent/bootstrap4-
toggle@3.6.1/css/bootstrap4-toggle.min.css"
          rel="stylesheet">
    <!-- Styles -->
    <style>
        /*! normalize.css v8.0.1 | MIT License |
github.com/necolas/normalize.css */
        html {
            line-height: 1.15;
            -webkit-text-size-adjust: 100%
        }

        body {
            margin: 0
        }

        a {
            background-color: transparent
        }

        [hidden] {
            display: none
        }

        html {
            font-family: system-ui, -apple-system, BlinkMacSystemFont, Segoe UI,
Roboto, Helvetica Neue, Arial, Noto Sans, sans-serif, Apple Color Emoji, Segoe
UI Emoji, Segoe UI Symbol, Noto Color Emoji;
            line-height: 1.5
        }
```

```
*, :after, :before {
    box-sizing: border-box;
    border: 0 solid #e2e8f0
}

a {
    color: inherit;
    text-decoration: inherit
}

svg, video {
    display: block;
    vertical-align: middle
}

video {
    max-width: 100%;
    height: auto
}

.bg-white {
    --bg-opacity: 1;
    background-color: #fff;
    background-color: rgba(255, 255, 255, var(--bg-opacity))
}

.bg-gray-100 {
    --bg-opacity: 1;
    background-color: #f7fafc;
    background-color: rgba(247, 250, 252, var(--bg-opacity))
}

.border-gray-200 {
    --border-opacity: 1;
    border-color: #edf2f7;
    border-color: rgba(237, 242, 247, var(--border-opacity))
}

.border-t {
    border-top-width: 1px
}

.flex {
    display: flex
}

.grid {
    display: grid
}

.hidden {
    display: none
}

.items-center {
```

```
    align-items: center
}

.justify-center {
    justify-content: center
}

.font-semibold {
    font-weight: 600
}

.h-5 {
    height: 1.25rem
}

.h-8 {
    height: 2rem
}

.h-16 {
    height: 4rem
}

.text-sm {
    font-size: .875rem
}

.text-lg {
    font-size: 1.125rem
}

.leading-7 {
    line-height: 1.75rem
}

.mx-auto {
    margin-left: auto;
    margin-right: auto
}

.ml-1 {
    margin-left: .25rem
}

.mt-2 {
    margin-top: .5rem
}

.mr-2 {
    margin-right: .5rem
}

.ml-2 {
    margin-left: .5rem
}
```

```
.mt-4 {
    margin-top: 1rem
}

.ml-4 {
    margin-left: 1rem
}

.mt-8 {
    margin-top: 2rem
}

.ml-12 {
    margin-left: 3rem
}

.-mt-px {
    margin-top: -1px
}

.max-w-6xl {
    max-width: 72rem
}

.min-h-screen {
    min-height: 100vh
}

.overflow-hidden {
    overflow: hidden
}

.p-6 {
    padding: 1.5rem
}

.py-4 {
    padding-top: 1rem;
    padding-bottom: 1rem
}

.px-6 {
    padding-left: 1.5rem;
    padding-right: 1.5rem
}

.pt-8 {
    padding-top: 2rem
}

.fixed {
    position: fixed
}
```

```
        .relative {
            position: relative
        }

        .top-0 {
            top: 0
        }

        .right-0 {
            right: 0
        }

        .shadow {
            box-shadow: 0 1px 3px 0 rgba(0, 0, 0, .1), 0 1px 2px 0 rgba(0, 0, 0,
.06)
        }

        .text-center {
            text-align: center
        }

        .text-gray-200 {
            --text-opacity: 1;
            color: #edf2f7;
            color: rgba(237, 242, 247, var(--text-opacity))
        }

        .text-gray-300 {
            --text-opacity: 1;
            color: #e2e8f0;
            color: rgba(226, 232, 240, var(--text-opacity))
        }

        .text-gray-400 {
            --text-opacity: 1;
            color: #cbd5e0;
            color: rgba(203, 213, 224, var(--text-opacity))
        }

        .text-gray-500 {
            --text-opacity: 1;
            color: #a0aec0;
            color: rgba(160, 174, 192, var(--text-opacity))
        }

        .text-gray-600 {
            --text-opacity: 1;
            color: #718096;
            color: rgba(113, 128, 150, var(--text-opacity))
        }

        .text-gray-700 {
            --text-opacity: 1;
            color: #4a5568;
            color: rgba(74, 85, 104, var(--text-opacity))
```

```
}

.text-gray-900 {
    --text-opacity: 1;
    color: #1a202c;
    color: rgba(26, 32, 44, var(--text-opacity))
}

.underline {
    text-decoration: underline
}

.antialiased {
    -webkit-font-smoothing: antialiased;
    -moz-osx-font-smoothing: grayscale
}

.w-5 {
    width: 1.25rem
}

.w-8 {
    width: 2rem
}

.w-auto {
    width: auto
}

.grid-cols-1 {
    grid-template-columns:repeat(1, minmax(0, 1fr))
}

@media (min-width: 640px) {
    .sm\:rounded-lg {
        border-radius: .5rem
    }

    .sm\:block {
        display: block
    }

    .sm\:items-center {
        align-items: center
    }

    .sm\:justify-start {
        justify-content: flex-start
    }

    .sm\:justify-between {
        justify-content: space-between
    }

    .sm\:h-20 {
```

```
        height: 5rem
    }

    .sm\:ml-0 {
        margin-left: 0
    }

    .sm\:px-6 {
        padding-left: 1.5rem;
        padding-right: 1.5rem
    }

    .sm\:pt-0 {
        padding-top: 0
    }

    .sm\:text-left {
        text-align: left
    }

    .sm\:text-right {
        text-align: right
    }
}

@media (min-width: 768px) {
    .md\:border-t-0 {
        border-top-width: 0
    }

    .md\:border-l {
        border-left-width: 1px
    }

    .md\:grid-cols-2 {
        grid-template-columns:repeat(2, minmax(0, 1fr))
    }
}

@media (min-width: 1024px) {
    .lg\:px-8 {
        padding-left: 2rem;
        padding-right: 2rem
    }
}

@media (prefers-color-scheme: dark) {
    .dark\:bg-gray-800 {
        --bg-opacity: 1;
        background-color: #2d3748;
        background-color: rgba(45, 55, 72, var(--bg-opacity))
    }

    .dark\:bg-gray-900 {
        --bg-opacity: 1;
```

```
                background-color: #1a202c;
                background-color: rgba(26, 32, 44, var(--bg-opacity))
            }

            .dark\:border-gray-700 {
                --border-opacity: 1;
                border-color: #4a5568;
                border-color: rgba(74, 85, 104, var(--border-opacity))
            }

            .dark\:text-white {
                --text-opacity: 1;
                color: #fff;
                color: rgba(255, 255, 255, var(--text-opacity))
            }

            .dark\:text-gray-400 {
                --text-opacity: 1;
                color: #cbd5e0;
                color: rgba(203, 213, 224, var(--text-opacity))
            }

            .logo {
                border-radius: 50%;
            }
        }
    </style>

    <style>
        body {
            font-family: 'Nunito';
        }
    </style>
</head>
<body class="antialiased">
<div class="relative flex items-top justify-center min-h-screen bg-gray-100
dark:bg-gray-900 sm:items-center sm:pt-0">
    @if (Route::has('login'))
        <div class="hidden fixed top-0 right-0 px-6 py-4 sm:block">
            @auth
                <a href="{{ url('/home') }}" class="text-sm text-gray-700
underline">Home</a>
            @else
                <a href="{{ route('login') }}" class="text-sm text-gray-700
underline">Login</a>

                @if (Route::has('register'))
                    <a href="{{ route('register') }}" class="ml-4 text-sm text-
gray-700 underline">Register</a>
                @endif
            @endauth
        </div>
    @endif

    <div class="max-w-6xl mx-auto sm:px-6 lg:px-8 text-center">
```

```
    <img src="{{asset('img/DeusTerra.png')}}"
                              class="logo"
                              alt="Deus Terra">
    <h1 style="color: #aaaaaa">DeusTerra</h1>
    </div>
</div>
</body>
</html>
```